

DRIVER HGX 15W-40

Automotive

Description

Multigrade lubricant oil designed for use in light petrol vehicles. Recommended for petrol engines that require API SL quality level.

Properties

- Multigrade oil that keeps the engine clean.
- Its formulation minimises the formation of deposits and sludge.
- Protects the engines metal parts against corrosion.
- Suitable for vehicles that use CNG or LPG as fuel.

Quality levels, approvals and recommendations

- API SL

Technical specifications

	UNIT	METHOD	VALUE
SAE Grade			15W-40
Density at 15 °C	g/mL	ASTM D 4052	0,874
Viscosity at 100 °C	cSt	ASTM D 445	14
Viscosity at 40 °C	cSt	ASTM D 445	100
Viscosity at -20 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	143
Flash point, open cup	°C	ASTM D 92	215 min.
Pour point	°C	ASTM D 97	-39
T.B.N.	mg KOH/g	ASTM D 2896	6
Bosch Injector Shearing: Viscosity at 100 ° C after shear	cSt	CEC-L-14-93	12,5 min.
Noack volatility, 1hr at 250 °C	% weight	CEC-L-40-93	15 max.
HTHS, viscosity at 150 °C	cP	CEC-L-36-90	3,7 min.

The above mentioned characteristics are typical values and should not be considered product specifications.