

PRODUCT INFORMATION



Lubricants - Engine Oil - Marine Motor Oils

Version: 451/06a

Valvoline™ Valmarin TP-1230

Valmarin TP-1230 is a premium heavy duty motor oil, especially designed for medium and high speed marine trunk piston gasoil and marine diesel engines. Valmarin TP-1230 prevents ring-sticking, wear, and deposits formation and keeps the engine clean. Valmarin TP-1230 fulfils the requirements of most major marine diesel engine manufacturers.

Performance levels: SAE 30

API CF
MAK
MAN B&W
SEMT Pielstick
New Sulzer Diesel
Wärtsila

Applications

Suitable for heavy duty marine engines where single grade motor oils are recommended.

Medium & High speed trunk piston marine engines

Can often be used for deck machinery.

Diesel engines of generators.

Construction equipment.

Available in viscosity 30 and 40.

Features & Benefits

Wear protection

Strong oil film protects the engine against wear and corrosion, prevents ring-sticking.

Engine cleanliness

Keeps the engine clean and in good condition. Prevents deposits forming.

Break Down resistance

Thermal and Oxidation stable oil film, build up with a special marine additive system.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valmarin TP-1230	
SAE Viscosity Grade	30
Viscosity, mm ² /s @ 100 °C. ASTM D-445	11,6
Viscosity, mm ² /s @ 40 °C. ASTM D-445	96
Viscosity Index ASTM D-2270	109
TBN, mg KOH/g ASTM D-2896	12,9
Pour Point, °C ASTM D-5949	-36
Specific Gravity @ 15.6°C. ASTM D-4052	0,875
Flash Point, COC, °C. ASTM D-92	224

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 451/05a

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.