



specialty lubricants



Quality is in our nature

Eurol Additive-S Engine

Highly concentrated Syngis additive

Description:

Eurol Additive-S Engine is a mix of specially selected Eurol Syngis additives. It is mainly developed to give an engine oil extra performance, resulting in heavily loaded diesel running more efficient, more powerful and with an extra protection against wear. It does not contain chlorine or PTFE and can effortlessly replace chlorinated paraffin or PTFE microplastic-containing additives. Eurol Additive-S Engine can be added to engine oils used in heavily loaded diesel engines. It increases the EP performance spectacularly. By lowering the friction coefficient, energy is saved and engine power output is increased.

Instructions for use:

- Shake well before use
- First change heavily polluted oil and/or oil filters
- Add approximately 5% additive to the new oil
- Contact us for a dedicated advice

Eurol Additive-S Engine has the following characteristics:

- For heavily loaded diesel engines in e.g. earthmoving equipment, ships and generators
- Provides unparalleled extreme pressure properties and protects against wear
- Environmentally friendly and safe in use
- Very low friction coefficient
- Reduces energy consumption
- Increases power output
- Free from chlorinated paraffins or PTFE microplastics
- Economical in use

Physical properties:

Colour	Brown		
Flash point	150	°C	ASTM D 93

Version 1.0, 18-06-2019

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com