



specialty lubricants



Quality is in our nature

Eurol Chain Lube S-AC 38 FD

Chain / rope lubricant for the food industry

Description:

Eurol Chain Lube S-AC 38 FD with Eurol SYNGIS Technology is developed for the lubrication in the food and pharmaceutical industry of chains, ropes, joints and for applications where excellent lubrication, creeping and penetration properties are required. Especially suitable for sewing machines.

Instructions for use:

- Clean and degrease parts thoroughly
- Shake well before use
- Apply a thin film by brush
- Allow the product to penetrate
- Remove excess product with a clean cloth
- Eurol Chain Lube S-AC 38 FD can be used in a temperature range from -20°C to +80°C

Eurol Chain Lube S-AC 38 FD has the following characteristics:

- InS H1, 1797231
- Excellent anti wear properties
- Excellent protection against corrosion
- Very good water repellent properties
- Very good creeping and penetration properties
- Loosens corroded and stuck parts
- Low friction coefficient
- Reduces energy consumption
- Economical in use

Physical properties:

Colour	Yellow		
Density at 20°C	0.937	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	32	cSt	ASTM D 445
Viscosity, kinematic at 100°C	6.5	cSt	ASTM D 445
Viscosity Index	162		ASTM D 2270

Industrial oils - Chain - S001101
Version 1.0, 05-10-2015

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com