



specialty lubricants



Quality is in our nature

Eurol Grease CS-00/101-S FD

Semi fluid hybrid heavy duty gear box lubricant for the food industry

Description:

Eurol Grease CS-00/101-S FD has been designed for the lubrication of heavily loaded gearboxes and transmission. It is a synthetic lubricant of the newest generation and contains a high dose of Eurol Syngis Technology capable of withstanding high loads and providing excellent anti corrosion and unique anti wear protection. This extremely water resistant semi fluid lubricant does not dry out and has excellent stability when used in gearbox applications in e.g. fishery, agriculture and production of food products and other areas where gearboxes or transmissions are operating in steamy, wet, muddy or dusty conditions. Also very useful for the lubrication of chains and cables.

Instructions for use:

- Before applying the lubricant, clean the gearbox, automatic lubricator or part thoroughly
- Suitable for most automatic lubricators
- Contact your local Eurol sales specialist for additional instructions and application advice

Eurol Grease CS-00/101-S FD has the following characteristics:

- InS H1, 1797534
- Excellent anti corrosion properties
- Unique anti wear properties
- Capable of neutralising small amounts of water
- Very water (steam) resistant
- Resistant to sun / UV light
- Does not dry out
- Very shear stable
- Very heat stable
- Sticks to a surface when applied
- Stable in automatic lubricators
- Helps preventing oil leakage from gearboxes
- Lowers the temperature of the gearbox
- Very low friction coefficient
- Lowers energy consumption

Physical properties:

Colour	Beige		
NLGI consistency	00		ASTM D 217
Thickener type	Calcium Sulfonate		
Base oil viscosity	150	cSt	ASTM D 445
Base Oil Type	Synthetic		
Operating temperature	-35 - 145	°C	

Greases - Food - S005114
Version 1.0, 16-11-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com