



specialty lubricants



Quality is in our nature

Eurol Grease PL FD

Multifunctional transparent grease with Eurol Syngis Technology

Description::

Multipurpose transparent grease with Eurol Syngis Technology. Very suitable for the general grease lubrication of machines in the food industry where incidental food contact cannot be avoided. Provides anti corrosion properties and resists water, steam and alkaline cleaners. It has a long service life in wet areas and can be used to safely extend re-lubrication intervals. Thanks to the transparent nature of the grease, machine parts are easy to inspect.

Instructions for use:

- Clean and degrease parts thoroughly
- Apply a thin film
- Allow the product to penetrate and dry
- Remove excess product with a clean cloth
- For more demanding applications Eurol Grease CS-2 / 102 FD is a good alternative

Eurol Grease PL FD has the following characteristics:

- InS H1, 1797647
- Multifunctional grease for many applications
- Contains Eurol Syngis Technology
- Suitable for incidental food contact
- Transparent so machine parts are easy to inspect
- Colorless for clean lubrication
- Resistant to water, steam and alkaline cleaners
- Very good anti corrosion properties
- Extends lubrication service intervals
- Very low friction coefficient
- Reduces energy consumption
- Economical in use

Physical properties:

Colour	Colourless _EIGA0755		
NLGI consistency	2		ASTM D 217
Base oil viscosity	80	cSt	ASTM D 445
Base Oil Type	Pharmaceutical white oil		
Operating temperature	-20 – 150	°C	

Greases - S005190
Version 1.0, 21-03-2017

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com